



Ultralast Clear Anti Slip

Introduction:

Our Anti Slip is of the highest quality water borne pure acrylic emulsion floor coating with a minimum CSIRO R12 rating. An elastomeric one-way membrane used on any flooring where safety is a concern; concrete, timber, steel even tiles. It is an excellent alternative to epoxy floor coating with the added benefit of slip rating to an angle 30.7 degrees. It dries almost clear and can in fact be used over existing epoxy coatings.

The Ultralast Clear Anti slip great advantage is our non abrasive texture with the Ultralast key features; enhancing the protection, facilitating its maintenance and prolonging the life of the substrate. We live to our high standards of safety and environmental sustainability.

Applications:

Ultralast Clear Anti Slip can also be used on its own or on any of our final top coats to provide limitless solutions for any surface.

Ideal for use in:

- Hospitals – vinyl flooring, tiled ramps, etc
- Shopping mall ramps, stairs
- Restaurants and kitchen areas
- Fast food outlets
- Train stations
- Slippery timber platforms subjected to rain
- Jetties and sea side walkways,
- School areas
- Preserving the concrete look and preventing fungal and bacterial growth
- Child care and retirement facilities

Preparation:

All surfaces must be thoroughly cleaned and free of any loose particles. Refer to preparation section.

Technical info:

- Storage conditions Room (moderate) temperature, tightly closed (sealed)
- Colour range as per colour chart
- Shelf life 7 years +
- Temperature tolerance -50°C to 230°C
- Physical form Liquid
- Min. application temp 5°C

Remarks:

Clean all equipment thoroughly with water immediately after use.

Disposal of waste:

Any remaining paints in containers that are no longer required should be left in the container to dry for the next day. Paint will peel in a solidified sheet. It is environmentally friendly and non toxic and can be disposed off in normal waste disposal.