



HEAD OFFICE: Unit 46, 378 Parramatta Rd, Homebush West Sydney NSW 2140 AUSTRALIA [www.ultralast.com.au](http://www.ultralast.com.au)  
Ph. +61 2 8338 9997 Fax. +61 2 8338 9927 Email. [info@ultralast.com.au](mailto:info@ultralast.com.au)



## Ultralast texture coat

### **Introduction:**

Ultralast **TEXTURE COAT** is a Non-Toxic environmentally friendly high performance acrylic interior and exterior premium water based coating. This unique silicon modified pure emulsion **TEXTURE COAT** has been engineered to act as a one-way membrane, allowing moisture to escape to the surface but prevents moisture ingress into the treated substrate.

It is designed for fast and efficient application providing both **PROTECTION** and **STYLE** to any substrate. When cured Ultralast **TEXTURE COAT** has excellent bonding and flexibility properties that forms a tough protective film over the substrate allowing protection against extreme tropical conditions such as high rainfall, heat, moisture, UV rays, micro organisms, abrasion and chemical exposure while allowing to flex to resist minor cracking while staying safe and easy to apply compared to conventional paint. **DEPENDING ON APPLICATION FINISH CAN BE ANYWHERE FROM LOW PROFILE TO BOLD GRANULAR TEXTURE PROFILE.**

### **Applications:**

Ultralast **TEXTURE COAT** is typically applied as a decorative finish on walls and ceilings, it is ideal for obscuring building defects over a prolonged period of time. Ultralast **TEXTURE COAT** can be applied internally and externally and with zero VOC and non toxic content should be the coating of choice. Ultralast **TEXTURE COAT** does not host dirt and gives off no toxic emissions.

Recommended applications:

- Hospitals
- Domestic homes where asthmatics and those with hyper-sensitivities and allergies are a problem
- Daycare centers
- Restaurants, cafes, bars, hotels etc
- Walls and floors as Ultralast does not host dirt and gives off no toxic emissions

As a textured paint, Ultralast Texture coat has demonstrated good acoustic absorption properties. Apply on walls/ceilings as required.

### **Preparation:**

All surfaces must be thoroughly cleaned and free of any loose particles. Refer to preparation section.

**Technical info:**

- Storage conditions Room (moderate) temperature, tightly closed (sealed)
- Colour range as per colour chart
- Shelf life 7 years +
- Temperature tolerance -50°C to 230°C
- Physical form Liquid
- Min. application temp 5°C

**Remarks:**

Clean all equipment thoroughly with water immediately after use.

**Disposal of waste:**

Any remaining paints in containers that are no longer required should be left in the container to dry for the next day. Paint will peel in a solidified sheet. It is environmentally friendly and non toxic and can be disposed off in normal waste disposal.